

NEW ADDITIONS



4 LEG DOME with HOLE

Stable Forces per Batch Number

Excellent Tactile Effect

100% Traceability per Batch Number

Competitive Pricing

Superior Quality

**Used in a multitude of Industries, such as:
Membrane Switch, Automotive, Consumer
Electronics, Medical, Appliance, etc**

Suitable for LED Lighting

RoHS Compliant

Contact Configuration	SPST, Normally Open	Contact Resistance with Gold or Silver Plating	<100 ohms
Contact Bounce (on)	<0.3ms	Voltage/Current Maximum	<1 ohm
Contact Bounce (off)	<6ms	Breakdown Voltage	12mA @ 24 Volts DC, RL
Operating Temperature	-55°C to 125°C	Material	Over 200 Volts
Storage Temperature	-55°C to 125°C	Life Expectancy	Stainless Steel Type 304
Humidity	0-97% (no condensation)		Up to 1 Million

	Part No	Force	Size	Dimensions (mm)				
				Thickness	A	B	C	D Hole Ø
	MD 8.4 4 LLL-H-280N	280g	8.4mm	0.08	8.4	1.79	0.45	1.8
	MD 8.4 4 LLL-H-400G	400g	8.4mm	0.10	8.4	1.79	0.48	1.8
	MD 10 4 LEG-H-280N	280g	10.0mm	0.10	10.0	2.28	0.45	2.5
	MD 10 4 LEG-H-280G	280g	10.0mm	0.10	10.0	2.28	0.52	2.5
	MD 10 4 LEG-H-400N	400g	10.0mm	0.10	10.0	2.28	0.52	2.5
	MD 12 4 LEG-H-350N	350g	12.0mm	0.10	12.0	2.12	0.63	3.0
	MD 12 4 LEG-H-350G	350g	12.0mm	0.10	12.0	2.12	0.63	3.0
	MD 14 4 LEG-H-400N	400g	14.0mm	0.12	14.0	2.79	0.72	3.5

Plating Suffix at end of Part Number: N = Nickel, G = Gold

MEMCON (Asia) Limited
Units 5/6 6/F Westley Square
48 Hoi Yuen Rd Kwun Tong Hong Kong
T +852 3741 1411 F +852 3747 8980
www.memcon.asia sales@memcon.asia

MEMCON Limited
Unit 8 Campus Five Third Avenue Letchworth
Hertfordshire SG6 2JF United Kingdom
T +44 (0) 1462 371477 F +44 (0) 1462 677499
www.memcon.eu sales@memcon.eu

MEMCON North America
6000 Red Arrow Hwy Unit I
Stevensville Michigan 49127 USA
T +1 269 281 0478 F +1 269 593 5952
www.memcon.net sales@memcon.net